


# NON-RETURN VALVE / ANTI-FLOODING SYSTEM


# REDI

## Standards

Valve range from Ø100 to Ø200 is fully complying to **EN 13564**



**NORMAL WORKING  
SITUATION**



**EFFECTIVE ANTI-FLOODING**



Ø 110 (solvent cement)



Ø 160 (solvent cement)



Ø 200 (solvent cement)




Ø 250 (solvent cement)

Ø 315 (rubber ring)

Ø 400 (rubber ring)


# INSTALLATION DETAILS

Every valve is delivered in single carton box including installation instructions




## INSTALLATION

Ensure the valve is set horizontally, as it already has a built-in fall. Beware of the direction of flow as indicated by the arrow on the cover of the valve.




## OPERATION

The Redi anti-flooding device for use in horizontal pipes closes the pipeline automatically when backflow occurs. Ensure the handle is on the "OPEN".





## EMERGENCY CLOSURE DEVICE

The option exists to lock the valve in the "CLOSED" position for added security (no through drainage allowed).



## MAINTENANCE

The emergency closure device should ideally be tested once every six months. In case of dirt and deposits, remove the cover, clean parts, check gaskets and replace any damaged parts. We strongly recommend a complete servicing at least once every twelve months.



Officially Distributed by:



# EMERALD VINYL CORPORATION

Plant: 24 Oliveros Drive, Balintawak, Quezon City, Philippines

Tel. nos.: 8361-6101 Fax no.: 8361-6740

sales@emeraldvinyl.com